



Datenblatt ON4800

- Der ON4800 ist ein lüfterloser, wartungsfreier Server/Router (mobile Datacenter-in-a-Box) für alle OnBoard-Anwendungen im Transportwesen, zum Beispiel in Bussen und Zügen.
- Dank Virtualisierung (VM, Container) können mehrere Anwendungen wie Fahrgastinformation, Entertainment, Fahrgastzählung, Speicherung von Überwachungsdaten auf der gleichen Hardware und gleichzeitig betrieben werden.
- Hochperformante Intel 8 Core x86-64 CPU
- Umfangreiche Kommunikationsschnittstellen: VGA, 4 x PoE Gig ETH, 1 x Gigabit Ethernet, GPS/GNSS, bis zu 2 x 4G/5G Mobilfunk, 802.11ac, Wi-Fi 5/6, RS232 usw.
- Quality-of-Service sowie Firewall-Funktionalitäten sorgen dafür, dass unterschiedliche Sicherheits- und Kapazitätsanforderungen jederzeit erfüllt werden können.
- Automatisches «Zero Touch»-Deployment ab Werk, das heisst Geräte können direkt ab Produktion verbaut werden und es sind keine manuellen Konfigurationsarbeiten nötig (cloud-managed).
- Sicheres Übertragen der Nutzdaten über VPN (IPsec mit Zertifikaten)



Anwendungen

- Ideale Basisinfrastruktur für Bordrechner, Passagier-Informationssystem, Infotainment, usw.
- Kommunikationszentrale für Gigabit-schnelle (4G/5G) Fahrzeug-Land-Kommunikation
- Speicherung und Verwaltung von Überwachungsdaten (z.B. Videoüberwachung)

Features

- Intel® Core™ 9th Gen., 32 GB DDR4 DRAM
- WLAN, 4G/5G LTE, GNSS
- 2.5" HDD/SSD, NVMe storage
- Gigabit Ethernet, USB 3.0, DisplayPort, Audio
- RS232, RS422/RS485, IBIS

Performance

- > 1000 Mbps lokales Routing
- > 1000 Mbps VPN-Durchsatz über LTE/5G

Technische Daten ON4800

Dimensions (W x H x D): 260 x 256 x 110 mm
Weight: 6500 g,
depending on options
Operating temperature: -40 to +70 °C
Ingress Protection Level: IP65

CPU

Intel® Core™ 9th Gen. 8 cores, 8 Threads, up to 4.3 GHz, 12–25 W, 12 MB cache, 35 W

Memory

System RAM, SO-DIMM socket up to 32 GB/channel (64 GB for two channels)

Security

Trusted Platform Module 2.0

Mass Storage

- 2 x SSD/HDD 2.5" (SATA) external SSD/HDD
- 2 x mSATA 3.0

Wireless Functionality

- Dual-Modem support up to LTE CAT-20 and 5G
- Up to Dual-Band WiFi-6 (802.11ax) 2x2 MIMO
- GNSS receiver

Interfaces

This product includes interface options:

- Different wireless functions depending on assembled wireless interface cards
- Variable I/O in cutouts

SSD/HDD slot: 2 x 2.5" SATA 3.0 external SSD/HDD (compatible with 15 mm height), RAID 0/1 supported
2 x mSATA 3.0 (BIOS selection, occupied mPCIe slot)

Video: Chipset Intel® UHD graphics 360
1 x Waterproof VGA up to 1920 x 1200 @ 60 Hz

USB: 3 x USB 3.1

Ethernet: 1 x 10/100/1000BASE-T, iAMT + WOL, M12, X-coded, 4 x Independent LAN, 10/100/1000 Mbps
I210-IT GbE, PoE 802.3af/at, max. 60W

GPS/GNSS: 1 x U-blox NEO-M8N GNSS module for GPS/Glonass/QZSS/Galileo/Beidou
Optional U-blox NEO-M8U with dead reckoning

Expansions:

- 1 x Full size mini-PCIe socket (USB 2.0, PCIe 3.0/ SATA 3.0 (BIOS selection))
- 1 x Full size mini-PCIe socket (USB 2.0, PCIe 3.0/ SATA 3.0 (BIOS selection)), BOM optional full size mini-PCIe socket (USB 2.0) for LTE module with 2 x external SIM

- 1 x Full size mini-PCIe socket (USB 2.0) for LTE module, BOM optional M.2 3042 Key B socket (USB 2.0, USB 3.1 Gen2) for LTE/5G NR module with 2 x external SIM
- 1 x M.2 3042/3050/3052 Key B socket (USB 2.0, USB 3.1 Gen2) for LTE/5G NR module with 2 x external SIM
- 1 x M.2 3042/3050/3052 Key B socket (USB 2.0, USB 3.1 Gen2, PCIe 3.0 (BOM optional)) for LTE/5G NR module with 2 x external SIM

I/O Interface Front

21 x LED indicators (including 4 x programmable LED), 2 x externally accessible SIM card sockets per modem, 1 x Reset button, 2 x 2.5" external SSD/HDD, 12 x SMA antenna hole, 3 x USB 3.1 Gen1 type A (5V/1A) w/ cover, 1 x USB 3.1 Gen2 type A (5V/1A) w/ cover

I/O Interface Rear

4 x M12 X-coded PoE 802.3af/at, max. 60W, 1 x M12 X-coded LAN port, 10/100/1000 Mbps, 1 x Waterproof DC input connector with ignition, male, 1 x M8 for 1 x Mic-in, 1 x Line-out, 2 x Waterproof DB9 (COM1/COM2) for RS232 (isolation) 1 x Waterproof DB9 (COM3) for full RS232/422/485 (isolation), 1 x M12 A-coded 10pin (DIO)

- 4 x DI and 4 x DO (isolation)
 - Power in for DIO isolation, 9–36VDC 1 x M12 A-coded for 2 x USB 2.0
- 1 x VGA

Electrical Specifications

Power input 24–110 VDC w/ isolation
Reverse protection, OCP & UVP
Selectable boot-up & shut-down voltage for low power protection by software
Setting 8-level power on/off delay time by software
10–255 seconds WDT support, setup by software
SDK (Windows/Linux) including utility and sample code

Product Compliance: Rail-Rolling Stock

CE, FCC Class A, EN 50155: 2017

- Class OT4 (-40–70°C), 85°C for 10 minutes
 - Interruptions of voltage supply class S1, S2 (S2: 36–110VDC@70% load)
 - Supply change over class C1, C2
 - EMC EN 50121-1: 2017, EN 50121-3-2: 2016+A1: 2019
 - Environment EN 60068-2-1, EN 60068-2-2, EN 60068-2-30
 - Shock and vibration IEC 61373 Class B
 - Protective coating class PC1 (PC2, by request)
- EN 45545-2: 2013+A1:2015